



PrimaLuna®

EvoLution Series

Specifications

Model EVO 300 Hybrid Integrated Amplifier

Power 8 Ohm	>100 Watts per channel (typical 115 Watts)
Power 4 Ohm	>150 Watts per channel (typical 170 Watts)
Frequency Response	10 Hz – 80 kHz +/- 3 dB
THD	< 0.2% 100W @ 8 Ohm
S/N Ratio	-105dB (A-Weighted)
Input Impedance	34 kOhm
Input Sensitivity	415 mV
Total Gain (Pre + Power Amp)	37.2 dB (7dB + 30.2dB)
Power Consumption	99 Watts (no signal in); 645W@4R
Weight	Net weight: 59.5 lbs / 29 kg Shipping Weight: 68.3 lbs / 25 kg
Dimensions	15.9" x 15.2" x 8.1" / 405 x 385 x 205 mm (L x W x H)
Shipping Dimensions	22.7" x 18.4" x 12.4" / 578 x 468 x 316 mm (L x W x H)
Inputs	5 pairs Stereo RCA, 1 pair Home Theater Input
Outputs	Speaker Taps, Tape, Stereo/Mono Sub, Headphone
Tube Complement	6 x 12AU7
Damping Factor	160 (1 kHz)

All PrimaLuna products come with PrimaLuna Silver Label tubes which are pre-selected by us following our simple 60 out of 100 rule (PTS™ - Premium Tube Selection) and as such, are already “special” when compared to other standard tubes on the market.